



## LAMINAR AIR FLOW

LAMINAR AIR LOW WITH TOUCH  
SCREEN

DLAF-01

### SPESIFICATION:

Size: Overall dimension (WxDxH) mm 1350x800x2100  
Working zone (WxDxH) mm 1250 x 750 x 550

#### Touch Screen operating panel

Security : User password  
Pre -UV Timer : Selectable timer  
Air Select Speed : 3 steps  
ULPA Filter 6000 hours : Count Down hour  
UV Light 2000 hours : Count Down Hour

Real Time & date  
UV & filter Change remain indicator  
Filter : ULPA Filter efficiency 99.9995 %  
(0.1 um - 0.2 um)  
Pre Filter : Washable, Arrestance 80 - 85 %  
Net weight : ±145 kg  
Power : 315 W , Voltage 220 V /50 hz  
Vibration : < 3 um  
Noise Level : > 58 dba



#### Construction

Cabinet : Electrogalvanized steel White Oven  
baked epoxy-polyester powder- coated Finish

Sash : UV safe Polycarbonate

#### Air Flow system

Inside Volume of working space : 0.534 M<sup>3</sup>  
volume of treated air per hour : 1071 M<sup>3</sup> /H

**LAMINAR AIR FLOW**  
Type DLAF-01