

BARRIER WASHING MACHINE



FEATURE :

The basket is divided into two separate operating areas, clean and non-clean. The laundry is loaded from the door on the side of the non-clean area, and after washing, it is taken out from the door on the side of the clean area. Prevents cross-contamination of laundry due to loading and discharge from non-clean areas, making it an ideal solution for dust-free industrial and hospital laundry

Spesifikasi Mesin :

Model		DLA-B50	DLA-B100	DLA-B150
Capacity	Kg	50	100	150
Volume	L	506	1000	1500
Drum size	mm	905×862	1060×1225	1200×1328
Motor power	Kw	5.5	11	22
Washing speed	ajhas	40	30	30
Balancing speed	r/min	60	60	60
Mid-extract speed	r/min	340	340	340
High-extract speed	r/min	680	650	650
Steam pipe	r/min	DN25	DN25	DN25
Cold/ hot water pipe	mm	40(G1 1/2")	50(G 2")	50(G 2")
Compressed air pipe	mm	8	8	8
Compressed air pressure	Mpa	0.5-0.6	0.5-0.6	0.5-0.6
Water consumption	Kg	1200	1800	2200
Steam consumption	Kg	30	50	75
Power consumption	Kwh	2.1	3.2	5
Compressed air flow	m ² /min	0.36	0.36	0.36
Four core copper core	mm	6	10	12
(L×W×H) Dimension	mm	1795×1334×1928	2160×1484×2008	2550×1650×2200
Machine weight	Kg	1800	2800	3700
Heating Power	Kw	24	36	36