



DHARMA



VACCINE

SPEIFICATION	DCR-01	DCR-02
Construction	Stainless Steel Plate.	Stainless Steel Plate.
Handle door	Made stainless steel	Made stainless steel
Door	Double glass with a stainless steel framework	Double glass with a stainless steel framework
Insulation	High density Polyurethane Foamed	High density Polyurethane Foamed
Finishing	Epoxy powder coating and polished	Epoxy powder coating and polished
Temperature	2°C – 8°C	2°C – 8°C
Temp. Control	Microprocessor Control	Microprocessor Control
Defrost	Automatic	Automatic
Refrigerant	R134a	R134a
Voltage	250 Volt	90 Volt
Capacity	288 L	378 L
Equipped with	4pcs shelves, vertical light, lock	4pcs shelves, vertical light, lock
Dimensions W x L x H	58 x 61 x 183 cm	62 x 61 x 195 cm

REFRIGERATOR



DHARMA



VACCINE

SPEIFICATION	DVS-01	DVS-02	DVS-03
Construction	Steel Plate, ABS	Steel Plate, ABS	Steel Plate, ABS
Door Type	Single door	Single door	Single door
Finishing	Epoxy powder coating	Epoxy powder coating	Epoxy powder coating
Types & Dimensions	78 x 65 x 87 cm	104 x 65 x 87	122 x 71 x 87 cm
Power Consumption	116 Watt	141 Watt	193 Watt
Capacity	150 L	210 L	330 L
Temperature Range	0° ~ 8°C	0° ~ 8°C	0° ~ 8°C
Refrigerant	R600a	R600a	R600a
Equipped with	Digital temperature control Baskets, castors, lock & drainage	Digital temperature control Baskets, castors, lock & drainage	Digital temperature control Baskets, castors, lock & drainage

TYPE	CAPASITY
DCR-01	288L
DCR-02	378L
DVS-01	150L
DVS-02	210L
DVS-03	330L
DVS-04	150L
DVS-05	210L
DVS-06	330L
DVS-07	150L
DVS-08	210L
DVS-09	330L

STORAGE



DHARMA



VACCINE

SPEIFICATION	DVS-04	DVS-05	DVS-06
Construction	Steel Plate, ABS	Steel Plate, ABS	Steel Plate, ABS
Door Type	Single door	Single door	Single door
Finishing	Epoxy powder coating	Epoxy powder coating	Epoxy powder coating
Types & Dimensions	78 x 65 x 87 cm	104 x 65 x 87	122 x 71 x 87 cm
Power Consumption	116 Watt	141 Watt	193 Watt
Capacity	150 L	210 L	330 L
Temperature Range	-15° ~ -25°C	-15° ~ -25°C	-15° ~ -25°C
Refrigerant	R600a	R600a	R600a
Equipped with	Digital temperature control Baskets, castors, lock & drainage	Digital temperature control Baskets, castors, lock & drainage	Digital temperature control Baskets, castors, lock & drainage

TYPE	CAPASITY
DCR-01	288L
DCR-02	378L
DVS-01	150L
DVS-02	210L
DVS-03	330L
DVS-04	150L
DVS-05	210L
DVS-06	330L
DVS-07	150L
DVS-08	210L
DVS-09	330L

STORAGE



DHARMA



VACCINE

SPEISIFICATION	DVS-07	DVS-08	DVS-09
Construction	Steel Plate, ABS	Steel Plate, ABS	Steel Plate, ABS
Door Type	Single door	Single door	Single door
Finishing	Epoxy powder coating	Epoxy powder coating	Epoxy powder coating
Types & Dimensions	78 x 65 x 87 cm	104 x 65 x 87	122 x 71 x 87 cm
Power Consumption	116 Watt	141 Watt	193 Watt
Capacity	150 L	210 L	330 L
Temperature Range	-25° ~ 8°C	-25° ~ 8°C	-25° ~ 8°C
Refrigerant	R600a	R600a	R600a
Equipped with	Digital temperature control Baskets, castors, lock & drainage	Digital temperature control Baskets, castors, lock & drainage	Digital temperature control Baskets, castors, lock & drainage

TYPE	CAPASITY
DCR-01	288L
DCR-02	378L
DVS-01	150L
DVS-02	210L
DVS-03	330L
DVS-04	150L
DVS-05	210L
DVS-06	330L
DVS-07	150L
DVS-08	210L
DVS-09	330L

STORAGE